

Package: forestat (via r-universe)

October 9, 2026

Type Package

Title Forest Carbon Sequestration and Potential Productivity Calculation

Version 1.2.0

Description Include assessing site classes based on the stand height growth and establishing a nonlinear mixed-effect biomass model under different site classes based on the whole stand model to achieve more accurate estimation of carbon sequestration. In particular, a carbon sequestration potential productivity calculation method based on the potential mean annual increment is proposed. This package is applicable to both natural forests and plantations. It can quantitatively assess stand's potential productivity, realized productivity, and possible improvement under certain site, and can be used in many aspects such as site quality assessment, tree species suitability evaluation, and forest degradation evaluation. Reference: Lei X, Fu L, Li H, et al (2018) <[doi:10.11707/j.1001-7488.20181213](https://doi.org/10.11707/j.1001-7488.20181213)>. Fu L, Sharma R P, Zhu G, et al (2017) <[doi:10.3390/f8040119](https://doi.org/10.3390/f8040119)>.

License GPL (>= 3)

Maintainer Yuanyuan Han <jackhanyuan@foxmail.com>

URL <https://github.com/caf-ifrit/forestat>

BugReports <https://github.com/caf-ifrit/forestat/issues>

Encoding UTF-8

Language en-US

LazyData true

Depends R (>= 3.5.0)

RoxygenNote 7.3.2

Imports dplyr, ggplot2, graphics, nlme, stats, rlang

Suggests knitr, rmarkdown

VignetteBuilder knitr

NeedsCompilation no
Author Liyong Fu [aut], Shirong Liu [aut], Shouzheng Tang [aut],
Guangshuang Duan [aut], Zhong Wang [aut], Linyan Feng [aut],
Dongbo Xie [aut], Yuanyuan Han [aut, cre]
Repository <https://caf-ifr.it.r-universe.dev>
Date/Publication 2026-10-09 07:53:19 UTC
RemoteUrl <https://github.com/caf-ifr.it/forestat>
RemoteRef HEAD
RemoteSha f135c7f45c44706862741db588ef94b083ca8d2f
RemoteSubdir forestat

Contents

birch	2
calc_degraded_forest_grade	3
class.plot	4
degraded_forest_preprocess	5
FittingEvaluationIndex	6
forestData	7
larch	8
picea	9
plot.forestData	10
plot_1	11
plot_2	12
plot_3	12
potential.productivity	13
realized.productivity	14
summary.forestData	15
tree_1	16
tree_2	16
tree_3	17
Index	18

birch	<i>Birch Dataset</i>
-------	----------------------

Description

A dataset containing information about birch trees in the Winter Olympics core area.

Usage

birch

Format

A data frame with 2603 rows and 17 variables:

PLOT Numeric sample plot identifier.

TREE Tree species code; always "birch" in this dataset.

D Diameter at breast height (DBH) of the tree, in centimeters.

H Height of the tree, in meters.

CBH Crown base height (branch-free height), in meters.

LIFE Tree condition code: "alive", "broken_head", "dead", "healthy", "standing_dead", "unknown", or "withered_tip".

CW_E Horizontal crown extent from the stem toward the east, in meters.

CW_S Horizontal crown extent from the stem toward the south, in meters.

CW_W Horizontal crown extent from the stem toward the west, in meters.

CW_N Horizontal crown extent from the stem toward the north, in meters.

X Within-plot X-coordinate of the tree, in meters; missing coordinates are NA.

Y Within-plot Y-coordinate of the tree, in meters; missing coordinates are NA.

SD Stand density, in trees per hectare.

CLR Crown length ratio, calculated as crown length divided by tree height.

CW Mean crown diameter, calculated as the mean of CW_EW and CW_SN, in meters.

CW_EW East-west crown diameter, calculated as CW_E + CW_W, in meters.

CW_SN South-north crown diameter, calculated as CW_S + CW_N, in meters.

Details

Paired zero coordinates used as missing-value placeholders in the source records are represented as NA.

calc_degraded_forest_grade

Calculating degraded forest grade

Description

Calculation of degraded forest grade.

Usage

```
calc_degraded_forest_grade(plot_data)
```

Arguments

plot_data	Preprocessed plot_data
-----------	------------------------

Details

Calculation of degraded forest grade, including p1, p2, p3, p4, p5, p1m, p2m, p3m, p4m, Z1, Z2, Z3, Z4, Z5, Z, Z_weights, Z_grade, Z_weights_grade etc.

Value

res_data with degraded forest grade

Examples

```
# Load forest survey data
data(tree_1)
data(tree_2)
data(tree_3)
data(plot_1)
data(plot_2)
data(plot_3)

# Preprocess the degraded forest data
plot_data <- degraded_forest_preprocess(tree_1, tree_2, tree_3, plot_1, plot_2, plot_3)

# Calculation of degraded forest grade
res_data <- calc_degraded_forest_grade(plot_data)
```

class.plot

Calculate the site classes based on stand height growth

Description

class.plot adds new variables: the original height classes and the adjusted height classes. And the existing variables are retained.

Usage

```
class.plot(
  data,
  model = "Richards",
  interval = 5,
  number = 5,
  maxiter = 1000,
  H_start = c(a = 20, b = 0.05, c = 1),
  BA_start = c(a = 80, b = 1e-04, c = 8, d = 0.1),
  Bio_start = c(a = 450, b = 1e-04, c = 12, d = 0.1)
)
```

Arguments

data	A data.frame data in which at least four columns are required as input: ID, code, AGE, H.
model	Type of model used for building the H-model (stand height model), options are 'Logistic', 'Richards', 'Korf', 'Gompertz', 'Weibull', or 'Schumacher'.
interval	The initial stand age interval for height classes.
number	The maximum number of initial height classes.
maxiter	The maximum number of iterations to fit the H-model.
H_start	The initial parameters for fitting the H-model, the default value is $c(a=20, b=0.05, c=1.0)$.
BA_start	The initial parameters for fitting the BA-model, the default value is $c(a=80, b=0.0001, c=8, d=0.1)$.
Bio_start	The initial parameters for fitting the Bio-model, the default value is $c(a=450, b=0.0001, c=12, d=0.1)$.

Details

Input takes a data.frame with three variables ID, AGE, H and returns height classes of every sample (rows in the data.frame).

Value

A data of forestData class with output values, models and model parameters.

Examples

```
if (interactive()) {
# Load sample data
data("forestData")

# Build a model based on the forestData and return a forestData class object
forestData <- class.plot(forestData,model="Richards",
                        interval=5,number=5,maxiter=1000,
                        H_start=c(a=20,b=0.05,c=1.0))
}
```

degraded_forest_preprocess

Preprocess the degraded forest data

Description

Preprocess the degraded forest data and return the plot_data.

Usage

```
degraded_forest_preprocess(tree_1, tree_2, tree_3, plot_1, plot_2, plot_3)
```

Arguments

tree_1	Tree data for the 1st period
tree_2	Tree data for the 2nd period
tree_3	Tree data for the 3rd period
plot_1	Sample plot data for the 1st period
plot_2	Sample plot data for the 2nd period
plot_3	Sample plot data for the 3rd period

Details

tree_1, tree_2, tree_3 are required to include the fields "plot_id", "inspection_type", and "tree_species_code".
 plot_1, plot_2, and plot_3 are required to include the fields "plot_id", "standing_stock", "forest_cutting_stock", "crown_density", "disaster_level", "origin", "dominant_tree_species", "age_group", "naturalness", and "land_type".

Value

Preprocessed plot_data

Examples

```
# Load forest survey data
data(tree_1)
data(tree_2)
data(tree_3)
data(plot_1)
data(plot_2)
data(plot_3)

# Preprocess the degraded forest data
plot_data <- degraded_forest_preprocess(tree_1, tree_2, tree_3, plot_1, plot_2, plot_3)
```

FittingEvaluationIndex

Calculate Fitting Evaluation Indices

Description

This function calculates several fitting evaluation indices based on estimated and observed values.

Usage

```
FittingEvaluationIndex(EstiH, ObsH)
```

Arguments

EstiH A numeric vector of estimated values.
ObsH A numeric vector of observed values.

Details

EstiH and ObsH must have the same length. Non-finite pairs are removed, and at least two finite pairs are required. R2 is NA when all observed values are equal, and TRE is NA when all estimated values are zero.

Value

A named numeric vector with evaluation indices:

pe Mean error
RMSE Root Mean Squared Error
R2 Coefficient of determination
Var Variance of the error
TRE Total Relative Error (percentage)

Examples

```
FittingEvaluationIndex(c(1, 2, 4), c(1, 3, 5))
```

forestData	<i>Mixed birch-broadleaf forest data</i>
------------	--

Description

Mixed birch-broadleaf forest data

Usage

```
forestData
```

Format

‘forestData’ A data frame with 320 rows and 16 columns:

ID Plot ID
AGE The average age of the stand
H Stand height
BA Stand basal area
Bio Stand biomass
S Stand density index
code Forest type code of plot ...

larch

*Larch Dataset***Description**

A dataset containing information about larch trees in the Winter Olympics core area.

Usage

larch

Format

A data frame with 4538 rows and 18 variables:

PLOT Numeric sample plot identifier.

TREE Tree species code; always "larch" in this dataset.

D Diameter at breast height (DBH) of the tree, in centimeters.

H Height of the tree, in meters.

CBH Crown base height (branch-free height), in meters.

LIFE Tree condition code: "alive", "broken_head", "broken_tip", "healthy", or "unknown".

CW_E Horizontal crown extent from the stem toward the east, in meters.

CW_S Horizontal crown extent from the stem toward the south, in meters.

CW_W Horizontal crown extent from the stem toward the west, in meters.

CW_N Horizontal crown extent from the stem toward the north, in meters.

X Within-plot X-coordinate of the tree, in meters; missing coordinates are NA.

Y Within-plot Y-coordinate of the tree, in meters; missing coordinates are NA.

SD Stand density, in trees per hectare.

CLR Crown length ratio, calculated as crown length divided by tree height.

CW Mean crown diameter, calculated as the mean of CW_EW and CW_SN, in meters.

CW_EW East-west crown diameter, calculated as CW_E + CW_W, in meters.

CW_SN South-north crown diameter, calculated as CW_S + CW_N, in meters.

AGE.GROUP Age-group label stored in Chinese, with categories corresponding to young, middle-aged, near-mature, mature, and over-mature forest.

Details

Paired zero coordinates used as missing-value placeholders in the source records are represented as NA; an isolated zero is retained as a valid plot-boundary coordinate.

picea

*Qinghai Spruce Dataset***Description**

A dataset containing information about Qinghai spruce trees at the Xishui forest farm of Su'nan Yuguzu Autonomous County, China, in Gansu Qilian Mountain National Nature Reserve.

Usage

picea

Format

A data frame with 402 rows and 24 variables:

LIDAR-X Projected X-coordinate of the LIDAR-detected tree, in meters.

LIDAR-Y Projected Y-coordinate of the LIDAR-detected tree, in meters.

LH Tree height derived from LIDAR data, in meters.

LHCB Crown base height derived from LIDAR data, in meters.

LCW1 East-west crown diameter derived from LIDAR data, in meters.

LCW2 South-north crown diameter derived from LIDAR data, in meters.

LCW Mean LIDAR-derived crown diameter, calculated as the mean of LCW1 and LCW2, in meters.

CPA Crown projection area, in square meters.

X Projected X-coordinate of the ground-measured tree, in meters.

Y Projected Y-coordinate of the ground-measured tree, in meters.

Z Elevation of the tree base, in meters above sea level.

PLOT Character sample plot name, from "yd01" to "yd16".

PLOT1 Numeric sample plot identifier, from 1 to 16.

OBS Tree observation identifier.

D0 Ground-measured diameter at breast height (DBH), in centimeters.

H0 Ground-measured height of the tree, in meters.

HCB0 Crown base height (branch-free height) measured on the ground, in meters.

CW01 Ground-measured east-west crown diameter, in meters.

CW02 Ground-measured south-north crown diameter, in meters.

CW Mean ground-measured crown diameter, calculated as the mean of CW01 and CW02, in meters.

STEM Estimated biomass of the tree stem, in kilograms.

BRANCH Estimated biomass of the tree branches, in kilograms.

FOLIAGE Estimated biomass of the tree foliage, in kilograms.

FRUIT Estimated biomass of the tree fruit, in kilograms.

plot.forestData	<i>ForestData Plot</i>
-----------------	------------------------

Description

Plot graphs about the forestData.

Usage

```
## S3 method for class 'forestData'
plot(
  x,
  model.type = "H",
  plot.type = "Curve",
  xlab = NA,
  ylab = NA,
  legend.lab = "Site class",
  title = "Mixed birch-broadleaf forest",
  ...
)
```

Arguments

x	A data of forestData class.
model.type	Type of model used for fitting, options are 'H' (stand height growth model), 'BA' (stand basal area model), or 'Bio' (stand biomass model).
plot.type	Type of plot, options are 'Curve' (curve plot), 'Scatter_Curve' (scatter plot with curve), 'Residual' (residual plot), or 'Scatter' (scatter plot).
xlab	The title for the x axis.
ylab	The title for the y axis.
legend.lab	The title for the legends.
title	The text for the Plot title.
...	Additional arguments affecting the figure plotted.

Value

A trellis plot object

Examples

```
if (interactive()) {
  # Load sample data
  data("forestData")

  # Build a model based on the forestData and return a forestData class object
  forestData <- class.plot(forestData,model="Richards",
```

```

        interval=5,number=5,maxiter=1000,
        H_start=c(a=20,b=0.05,c=1.0))

# Plot the curve of the height classes
plot(forestData, model.type="H",
      plot.type="Curve",
      xlab="Stand age (year)",ylab="Height (m)",legend.lab="Site class",
      title="The H-model curve of the mixed birch-broadleaf forest")
}

```

plot_1

1st period sample plot survey data

Description

The 1st period sample plot survey data (e.g. 2005)

Usage

```
plot_1
```

Format

‘plot_1’ A data frame with 62 rows and 23 columns:

plot_id Plot ID

standing_stock Standing stock

forest_cutting_stock Forest cutting stock

crown_density Crown density

disaster_level Disaster level

origin origin

dominant_tree_species Dominant tree species

age_group Age group

naturalness Naturalness

land_type Land type ...

plot_2

2nd period sample plot survey data

Description

The 2nd period sample plot survey data (e.g. 2010)

Usage

plot_2

Format

‘plot_2’ A data frame with 100 rows and 5 columns:

plot_id Plot ID

standing_stock Standing stock

forest_cutting_stock Forest cutting stock

crown_density Crown density

disaster_level Disaster level

origin origin

dominant_tree_species Dominant tree species

age_group Age group

naturalness Naturalness

land_type Land type ...

plot_3

3rd period sample plot survey data

Description

The 3rd period sample plot survey data (e.g. 2015)

Usage

plot_3

Format

'plot_3' A data frame with 100 rows and 5 columns:

plot_id Plot ID
standing_stock Standing stock
forest_cutting_stock Forest cutting stock
crown_density Crown density
disaster_level Disaster level
origin origin
dominant_tree_species Dominant tree species
age_group Age group
naturalness Naturalness
land_type Land type ...

potential.productivity

Calculate the potential productivity.

Description

potential.productivity calculate the potential productivity of stand based on model parameters(obtained from the parameterOutput function).

Usage

```
potential.productivity(
  forestData,
  code = 1,
  age.min = 5,
  age.max = 150,
  left = 0.05,
  right = 100,
  e = 1e-05,
  maxiter = 50
)
```

Arguments

forestData	A forestData class data
code	Codes for forest types.
age.min	The minimum age of the stand.
age.max	The maximum age of the stand.
left	Solving for the left boundary of the potential productivity.

right	Solving for the right boundary of the potential productivity.
e	Accuracy parameters for solving the stand density index according to Newton's iterative method.
maxiter	Maximum number of iterations parameter for solving the stand density index according to Newton's iteration method.

Details

potential.productivity takes data_BA,data_V parameters as required inputs.

Value

A forestData class in which a data.frame with potential productivity parameters is added.

Examples

```
if (interactive()) {
# Load sample data
data("forestData")

# Build a model based on the forestData and return a forestData class object
forestData <- class.plot(forestData,model="Richards",
                        interval=5,number=5,maxiter=1000,
                        H_start=c(a=20,b=0.05,c=1.0))

# Calculate the potential productivity of the forestData object
forestData <- potential.productivity(forestData,code=1,
                                    age.min=5,age.max=150,
                                    left=0.05,right=100,
                                    e=1e-05,maxiter=50)
}
```

realized.productivity *Calculate the realized productivity.*

Description

realized.productivity calculate the realized productivity of each stand based on model parameters (obtained from the parameterOutput function).

Usage

```
realized.productivity(forestData, left = 0.05, right = 100)
```

Arguments

forestData	A forestData class data
left	Solving for the left boundary of the realized productivity.
right	Solving for the right boundary of the realized productivity.

Details

realized.productivity takes data,data_BA,data_V parameters as required inputs.

Value

A forestData class in which a data.frame with realized productivity parameters is added.

Examples

```
if (interactive()) {
# Load sample data
data("forestData")

# Build a model based on the forestData and return a forestData class object
forestData <- class.plot(forestData,model="Richards",
                        interval=5,number=5,maxiter=1000,
                        H_start=c(a=20,b=0.05,c=1.0))

# Calculate the realized productivity of the forestData object
forestData <- realized.productivity(forestData,left=0.05,right=100)
}
```

summary.forestData	<i>Summary of forestData</i>
--------------------	------------------------------

Description

Generates summary statistics for forestData objects.

Usage

```
## S3 method for class 'forestData'
summary(object, ...)
```

Arguments

object	A forestData object (after class.plot).
...	Additional arguments affecting the summary produced.

Details

The summary includes the summary of raw data, the model, the model parameters, potential productivity and real productivity in forestData(if available)

Value

A summary object of class "summary.forestData"

Examples

```
if (interactive()) {
# Load sample data
data("forestData")

# Build a model based on the forestData and return a forestData class object
forestData <- class.plot(forestData,model="Richards",
                        interval=5,number=5,maxiter=1000,
                        H_start=c(a=20,b=0.05,c=1.0))

# Get the summary data of the forestData object
summary(forestData)
}
```

tree_1	<i>1st period trees survey data</i>
--------	-------------------------------------

Description

The 1st period trees survey data (e.g. 2005)

Usage

tree_1

Format

‘tree_1’ A data frame with 1634 rows and 5 columns:

- plot_id** Plot ID
- inspection_type** Inspection type
- tree_species_code** Tree species code ...

tree_2	<i>2nd period trees survey data</i>
--------	-------------------------------------

Description

The 2nd period trees survey data (e.g. 2010)

Usage

tree_2

Format

‘tree_2’ A data frame with 4778 rows and 5 columns:

plot_id Plot ID

inspection_type Inspection type

tree_species_code Tree species code ...

tree_3	<i>3rd period trees survey data</i>
--------	-------------------------------------

Description

The 3rd period trees survey data (e.g. 2015)

Usage

tree_3

Format

‘tree_3’ A data frame with 4528 rows and 5 columns:

plot_id Plot ID

inspection_type Inspection type

tree_species_code Tree species code ...

Index

* datasets

- birch, [2](#)
- forestData, [7](#)
- larch, [8](#)
- picea, [9](#)
- plot_1, [11](#)
- plot_2, [12](#)
- plot_3, [12](#)
- tree_1, [16](#)
- tree_2, [16](#)
- tree_3, [17](#)

birch, [2](#)

calc_degraded_forest_grade, [3](#)

class.plot, [4](#)

degraded_forest_preprocess, [5](#)

FittingEvaluationIndex, [6](#)

forestData, [7](#)

larch, [8](#)

picea, [9](#)

plot.forestData, [10](#)

plot_1, [11](#)

plot_2, [12](#)

plot_3, [12](#)

potential.productivity, [13](#)

realized.productivity, [14](#)

summary.forestData, [15](#)

tree_1, [16](#)

tree_2, [16](#)

tree_3, [17](#)